

OPTOKON, a.s. ID: 13692283 VAT NO: CZ13692283 WWW.OPTOKON.COM OPTOKON@OPTOKON.COM Tel. +420 564 040 111 Červený Kříž 250 586 01 Jihlava Czech Republic

# **HY-526 Glue Gun For Invisible Fiber (Digital Display)**

## **Description:**

#### **FTTR Glue Gun:**

Invisible fiber cabling glue gun is suitable for FTTR indoor invisible fiber cabling hot melt glue fixed construction. Equipped with notched gluing mouth, stable gluing effect, also equipped with invisible fiber cable tray fixed column and fiber outlet slot, easy wiring, simplify the operation process.



#### **Features:**

- Glue and fiber come out together, it is a convenient, faster, more beautiful, more convenient and efficient wiring experience
- 360° adjustable nozzle: horizontal and vertical, flexible switching effectively solve the wiring in the process of Angle, dead Angle, corner problem
- 100-220°C temperature range, adjust the temperature according to their own use. 100 °C heating to ensure that the glue gun temperature interval operation, 220°C high temperature heating to make glue out fast, suitable for continuous operation

### **Specification**

Dimension	LxWxH: 280 x 80 x 245 mm (including battery height)		
Weight	1050 g		
Rated voltage of battery	21 V DC	Battery	10 lithium ions
Battery capacity	3000 mAh	Temperature control	Adjustable
<b>Charging Voltage</b>	21 V	Charging current	2 A
Charging time	About 5 hours	Warm-up time	Room temperature 6-8 minutes
Standby time	Fully charged for about 120 minutes	Maximum temperature	220 °C
Applicable rubber rod diameter	Ø 11 mm	Gun nozzle design	360° adjustable



EN ISO 9001:2015 EN ISO 14001:2015 Certified Company



Accredited Calibration Laboratory No. 2315 In Czech Republic & Malaysia

Accredited Testing Laboratory No. 1755











